


## DIN 3402

### Bilyalı Dişli Düz Tip Gresörlük B (K1) DIN 3402 180 °

Ball-Type grease nipples type B (K1) DIN 3402  
Straight version, zinc-plated steel.

SANLI ball-type nipples are suitable for all standard lubrication points, which have to be frequently lubricated in a reliably way. They are more and more often replaced by hydraulic-type grease nipples according to DIN 71412 due to their manifold application purposes.



GW thread  
L1 overall length  
L2 thread length  
SW HEX size  
(all measures in mm,  
thread metric or in inches)

Kod No.	GW	SW	L1	L2
2100703 B	M 6x0.75	7 mm	14 mm	5,5 mm
2100704 B	M 6x1.0	7 mm	14 mm	5,5 mm
2100905 B	M 7x1,0	9 mm	14 mm	5,5 mm
2100907 B	M 8x1.0	9 mm	14 mm	5,5 mm
2100908 B	M 8x1.25	9 mm	14 mm	5,5 mm
2101109 B	M10x1.0	11 mm	14 mm	5,5 mm
2101111 B	M10x1.5	11 mm	14 mm	5,5 mm
2101156 B	1/8 GAS	11 mm	14 mm	5,5 mm
2101457 B	1/4 GAS	14 mm	16 mm	6,5 mm
2101758 B	17 mm	3/8 GAS	17,5 mm	8 mm